Flockenhaus GmbH & Co. KG

FIXON® Fabric Stamping Ink LX T30

Application area

- For stamping on fabrics
- For permanent marking of textiles in a wide range of textile finishing processes (bleaching, dyeing, heat setting)

Product properties

- Chemical resistance equal to FIXON® Textile Marker
- Heat resistant up to 220 °C, pressure resistant (flatbed press)
- Resistant to peroxide and chlorine bleaching, HT dyeing, boiling 30 % caustic soda, boiling 20 % sulphuric acid, organic acids and soap-soda washing
- Smudge-proof and waterproof
- Colours: white, yellow, red

Handling instruction

- Shake well before use
- Always keep containers tightly closed after use
- Store in a cool, well-ventilated place protected from direct sunlight
- Always carry out a test on the respective material before use

Product data

- Base: synthetic resins, organic solvents and pigments
- Density at 20 °C: 0.93 g/cm³ (± 0.02)
- Flash point: < 23 °C
- Touch-dry after approx. 1 minute
- Shelf life: 2 years in the closed original container at room temperature
- Transport: UN 1263 Paint, class 3

Job safety

- Highly flammable liquid and vapour
- Causes serious eye irritation
- May cause drowsiness or dizziness
- Keep away from sources of ignition – no smoking; ensure good ventilation
- Wear safety goggles and protective gloves (butyl rubber)
- Keep out of the reach of children
- For further information see label and safety data sheet

Disposal instruction

- Dispose of in accordance with official regulations (waste code 20 01 27*)
- Completely emptied, uncontaminated packaging can be recycled.

Delivery form

Bottles 50 / 250 / 1000 ml – item no.:

- White: 6210 / 6211 / 6212
- Yellow: 6213 / 6214 / 6215
- Red: 6216 / 6217 / 6218

Technical data sheet

Further information on www.flockenhaus.de

Flockenhaus GmbH & Co. KG

Tel +49-661-72881 Fax +49-661-74933 Email: office@flockenhaus.de

Reviewed on 11.2026